

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 January 2001 (11.01.2001)

PCT

(10) International Publication Number
WO 01/02112 A1

(51) International Patent Classification⁷: B22C 1/02, 1/18

(21) International Application Number: PCT/KR00/00714

(22) International Filing Date: 4 July 2000 (04.07.2000)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
1999/027082 ✓ 6 July 1999 (06.07.1999) KR

(71) Applicant (for all designated States except US): **TECHNOLOGY UNION CO., LTD.** [KR/KR]; 58BL-11ot, Namdong Industrial Complex, 626, Kojan-dong, Namdong-ku, Incheon 405-310 (KR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HIROKAWA, Koji** [JP/JP]; 1053, Otamachi, Isesakishi, Gumma 372 (JP).

(74) Agent: **OH, Seung, Keon**; Dong Joo Building, 4th floor, 824-24, Yeoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 01/02112 A1

(54) Title: DISINTEGRATIVE CORE FOR HIGH PRESSURE CASTING, METHOD FOR MANUFACTURING THE SAME, AND METHOD FOR EXTRACTING THE SAME

(57) Abstract: Disclosed is a method for manufacturing a disintegrative core for use in high pressure casting. The disintegrative core can be applied where a light metal such as an aluminum alloy or magnesium alloy is subjected to high pressure casting, such as die casting or squeeze casting and is manufactured from a water-soluble salt which is high in latent heat and ranges, in melting point, from 280 to 520 °C and, in heat transfer coefficient (κ), from 9.8×10^{-2} to 1.2×10 W/m² °C. The water-soluble salt, alone or in combination with a fine hard powder, is melted and solidified in a core mold. Alternatively, the melt is processed into a fine powder which is then molded in a core mold. The method can be applied for the manufacture of complex shapes of cores. Also, disclosed is a method for extracting such a core from a high pressure molded product.